

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number  
**WO 2005/007522 A2**

(51) International Patent Classification<sup>7</sup>: **B65D 5/12, 3/10**

(21) International Application Number:  
PCT/US2004/022114

(22) International Filing Date: 12 July 2004 (12.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/486,160 10 July 2003 (10.07.2003) US

(71) Applicant (for all designated States except US): MEAD-  
WESTVACO CORPORATION [US/US]; One High  
Ridge Park, STAMFORD, CT 06905 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): GELARDI, John A.

[US/US]; P.O. BOX 714, Rocky Pasture, Kennebunkport,  
ME 04046 (US). MAZUREK, Richard [US/US]; 1031  
Roseland Avenue, Huntingdon, PA 19006 (US).


(74) Agents: DREW, Michael, V et al.; MEADWESTVACO  
CORPORATION, 299 Park Avenue, 13th Floor, New York,  
NY 10171 (US).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: PRODUCT PACKAGING WITH LATCHING ENDCAP AND METHOD FOR LOADING



(57) Abstract: A container includes a tube having a rim at one end defining an opening and an endcap including a channel that is shaped to receive the tube rim. The tube includes at least one latching aperture positioned such that when the tube rim is seated in the channel, the latching aperture is contained within the channel. The endcap further includes a latching member that engages the latching aperture when the tube rim is seated in the receiving channel. The latching member includes a sloped surface for deflecting the tube rim to allow the tube rim to be slid into position over the latching member. The endcap further includes a first guide fin assembly on a first side of the latching member and a second guide fin assembly on a second side of the latching member. Each of the first and second guide fin assemblies includes a sloped surface shaped to deflect the tube rim in a direction opposite to the deflection of the tube rim by the latching member when the tube rim is slid into position in the channel, and to maintain the engagement of the latching aperture by the latching member when the tube rim is seated in the channel.

WO 2005/007522 A2



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— without international search report and to be republished upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*